

# TEAK PROTECTION



## treatex<sup>®</sup>

Treatex Teak Protection is a solvent free exterior wood finish containing pigments which block damaging UV rays. This product is manufactured on a base of natural sustainable raw materials: linseed oil and sunflower oil. Treatex Teak Protection is designed for use on timbers like teak. It is not suitable for timbers which contain tannins, such as oak. Treatex Teak Protection is the ideal finish for garden furniture, boat decks and other exterior joinery.

- UV resistant
- Highly water resistant
- Solvent free
- Safe for use on children's toys
- Suitable for indoor and outdoor use
- Will not flake or peel





## Preparation

Treatex Teak Protection will only work on unfinished timber. Previous finishes must be fully removed prior to application. If timber is grey and weathered then it should be sanded back to restore its natural colour before application. Ensure the timber is dry and free from possible contaminants e.g. algae, grease, dirt, dust etc. We advise that when using Treatex Teak Protection, sufficient product is purchased to complete the whole project and when more than one tin is required it is advisable to mix them together before use. Timber must have a moisture content below 18%. Temperature must be greater than 8°C during application and drying. A trial application is essential prior to starting the project.

## Application of Treatex Teak Protection

Stir container thoroughly, before and during use. Use a brush to evenly apply Treatex Teak Protection in the same direction as the wood grain, allowing approximately 60–70ml per m<sup>2</sup>. This product works best when the second coat is applied 'wet on wet'. This means a second coat should be applied, in the same way as above, before the first coat is dry. After the second coat leave to dry for approximately 12 hours.

## Tips

We recommend a fresh coat is applied once a year. Treatex brushes are available. Wet brushes can be cleaned with warm soapy water. Store containers in a cool and frost free environment. Unopened containers will last for three years. Once containers are opened, transfer contents to a smaller airtight container.

## Coverage

1 litre covers approximately 15m<sup>2</sup> one coat depending on timber and method of application.

## Contact

Treatex Ltd, Unit I,  
Howland Road Business Park,  
Howland Road, Thame,  
Oxfordshire, OX9 3GQ.  
tel: 01844 260416  
fax: 01844 358160  
email: [info@treatex.co.uk](mailto:info@treatex.co.uk)  
[www.treatex.co.uk](http://www.treatex.co.uk)